

MONOBLOC Knee operating Handwash basin

Stainless steel AISI 304 L Completely monobloc

Easy to clean No joints

Easy mounting Easy to use



- AISI 304L stainless steel.
- 300 mm high Backsplash, 45° inclined top, 20 mm thickness.
- Dimensions of bowl: 280 mm x 400 mm 115 mm depth.
- Swan neck tap.
- Premixer hot and cold water.
- TEMPO STOP tap: 6 liters/ minute.
- Connexions hoses hot water / cold water.
- PVC U bend...





ALSO AVAILABLE WITH ELECTRONIC SENSOR TAP 🕨




ELECTRONIC MONOBLOC HANDWASH BASIN

Completely monobloc: Easy to clean, no joints and easy to assemble

- In AISI 304L stainless steel
- Battery-operated standalone handwash basin: 6V lithium-Battery (CPR2), service life: 125 000 uses per year for 3 years
- · Backsplash 300 mm high with sloped top 45 degrees
- Overall dimensions: high 470, width 480 mm, depth 360 mm
- Dimensions of bowl: 280 mm x 400 mm, depth 115 mm
- Mixer tap
- Usage pressure: 1 to 5 bars
- Output: 3l/min per integrated flow limiter
- 3/8" hot/cold water connector (12x17)
- PVC U bend







Ref. LMAMEDX

Ref. LMAME

HANDWASH STATION







Ref. LMASWTEX

- AISI 304L Stainless steel.
- 586 mm back splash, 30° inclined top, sifon
- Anti return valve.
- Pressed bowl 400 x 250 mm, depth 140 mm
- Premixer hot/cold water 1/2 inch
- Wall hanging integrated in the back splash
- Hygienic synthetic seal between the bowl and the back splash
- Paper towel dispenser. Soap dispenser. Bin



Hygiene

2 VERSIONS, 2 FINISHES:

- Knee operating tap: Pressure tap with knee operating tap behing the front panel Swivelling Swan neck tap with flexible stainless steel hose Outflow 6 liters/ minute Premixer: LMASWT and LMASWT with Stainless steel soapdispenser, paperdispenser and bin.
- Electronic sensor tap: Infrated sensor tap with electronic control 6 Volts Lithium battery Outflow 3 liters/ minute Mixer (Pictures): LMASWTE and LMASTEX with Stainless steel soapdispenser, paperdispenser and bin.



KNEE OPERATING HANDWASH BASIN

- In AISI 304L stainless steel
- With 240 mm high splashback at a 30° angle, flexible connection hose, U-bend, swan's neck tap, 1/2" hot/cold water connector
- Premixed hot/cold water (except LMASD)
- Non-return valve
- Push tap adjusted at the factory to: 6l/min



Protects the planet with its low water consumption.



- > Ergonomics: Knee operated panel suitable for any size of user
- > Hygiene: Splashback at a 30° angle, no retention of liquid
- > Hygiene: Completely round bowl

Round bowl Ø 305 mm x 150 mm



Rectangular bowl 400 x 250 x 140 mm



Handwash basin



Electronic handwash basin



Collective handwash basin

- In AISI 304L stainless steel
- No splashback, with plug and bend
- Rectangular pressed bowl, 1140 x 320 x 165 mm
- 2 swan's neck tap, 1/2" hot/cold water connector (LMAR)
- Non-return valve (Provide 2 Hot/cold water inlets) (LMAR)



ALSO AVAILABLE WITH ELECTRONIC SENSOR TAP



Hygiene



FOOT OPERATED INTEGRAL WASHBASIN



- In AISI 304L stainless steel
- Adjustable swan's neck tap with connection to the push button
- Foot operated pump
- Premixed hot/cold water 1/2" 15 x 21
- Non-return valve

cainless steel enser

Available with splashback + stainless steel soap dispenser + paper dispenser

STANDALONE HANDWASH BASIN





- In AISI 304L stainless steel
- Bowl same as LMASW
- Supplied with two 13 liters jerry can for clean and dirty water
- Foot operated pump
- Fitted with 2 wheels on the back to make it easy to move around



Ideal for:

> Rooms without a water inlet > Moves events (exhibitions...) **HEATING** standalone handwash basin



Ref. LMASWAC

HANDWASH BASIN ACCESSORIES















Hygiene

SOFINOR SAS P.A de la Houssoye Rue Ambroise Paré 59280 BOIS-GRENIER FRANCE

Tél: +33 3 20 10 34 10 Email: sofinor@sofinor.com

www.sofinor.com

