

**Safety in System**  
**Protection for man and machine**

# **FOOD AND BEVERAGES**

## **PRODUCT CATALOGUE**



# SAFE SOLUTIONS FOR YOUR INDUSTRY

## SAFETY SYSTEMS FOR THE FOOD-PROCESSING INDUSTRY

### THE BASIS: CUSTOMER ORIENTATION FROM THE START

Safety in system: Protection for man and machine – under this motto, the Schmersal Group develops and produces safety switching appliances and systems for the entire machinery and plant construction for decennia. In some industries, special and additional requirements are applicable. As a customer-focussed company, who intensively deals with the wishes of the manufacturers and users of machines, Schmersal has taken up these challenges from the start. As a result, specific products and solutions were developed for many industries and for some of them, a complete portfolio has been developed.

#### Various requirements

Harvesting, washing, drying, filleting, heating, shredding, mixing, filling, packing: the foodstuff production process has many process steps, which are generally taken over by machine automation. During these processes, the Machinery Safety directives and standards have to be observed. In addition to that, the foodstuff industry also has other fields of activity, which must be taken into account when selecting safety switchgear or command devices for the man-machine interface.

#### Hygiene

Hygiene is a key issue in the food-processing industry. Four hygienic zones can be distinguished, for which strictly defined constructive details of the “hygienic design” are applicable:

- Dry zone (non-contact area; protection against soiling required)
- Splashing zone (foodstuff can splash; the operators touch the foodstuff and the machines; risk of contamination or cross-contamination)
- Wet zone (high risk of bacterial contaminations; low-pressure cleaning with chemicals or hot cleaning)
- Aggressive zone (even higher risk of contamination; frequent hot steam cleaning or high-pressure cleaning with aggressive detergents)

The Hygienic Design also influences the choice of safety switchgear. An example: the food-processing industry was the first branch, which used safety sensors instead of the conventional electromechanical safety switches. These non-contact operating safety switchgears can be easily cleaned due to the smooth surfaces of the sensor and the actuator and moreover provide for concealed mounting.

#### Humidity, moisture and detergents

Stringent hygienic standards are applicable to those components or periphery of food-processing machinery, which are in contact with the product; as a result, the safety switchgear and actuating elements must meet the highest requirements as their degree of protection is regarded. Many series therefore are IP69K. These switchgears must be able to withstand a water jet of at least 80 bar with a temperature of 80 °C.

#### Temperature resistance

In frozen storage or in case of shock freezing – to name two examples – automated processes take place at temperatures below the freezing point. Even more frequent are the processes, for which high temperatures are inevitable, e.g. evaporation, homogenisation, drying, condensation, distillation. Switchgear, which are used for these processes, must be accordingly high- and low-temperature resistant.





### Branch-specific certifications

The specific characteristics to be featured by machinery and plants destined to the food-processing industry are laid down in different regulations, which also concern the individual machinery and plant components and which are in part very demanding. This includes, amongst others, the following norms and certification to the following standards:

- EN 1672-1 and EN 1672-2
- Ecolab
- EHEDG
- FDA

Switchgear from Schmersal is approved and certified in accordance with this regulation depending on the requirements.

### Long lifetime and availability

In food production, machinery and plants often operate with short cycles and in a three-shift operation in interlinked plants. The expected availability is accordingly high. Schmersal switchgear meet these requirements. They stand the test in various applications, even under unfavorable ambient conditions.

### Explosion protection

Organic dusts can present an explosive danger if the dust/air ratio falls within explosive limits. Therefore, the regulations of the dust explosion directive must be observed e.g. when filling/bottling and storing powdered food products and their primary products (flour, baking mixtures, pudding powder, coffee and cocoa powder). The Schmersal Group offers a comprehensive range of switchgear for automation and machine safety, which is approved and certified to the ATEX and IECEx Directives.

### Services

Machine safety is a complex topic. The Schmersal Group offers its customers comprehensive support for the implementation of standards and guidelines in high-productive machinery and plants. Included in the service portfolio are for example: seminars and the individual consultancy of the design engineers and safety engineers in more than 60 nations by certified Safety Consultants.

### Branch-related knowledge on call

The Schmersal Group aims at establishing good contacts and exchanging experiences with food-processing machinery builders, so that new safety solutions are developed and the individual consultancy is provided with the highest level of practice-orientation. To that effect, Schmersal is, amongst others, member of the "Packaging Valley Germany e.V." in Waiblingen. This Centre of Competence for packaging and automation technology reuniting many companies manufacturing machinery and plants for the food packaging industry.

# GUARD DOOR MONITORING

## AZM 300 – Solenoid interlock



- Intelligent door monitoring with a high level of protection against manipulation according to EN ISO 14119
- Symmetrical mounting for right- and left-hinged doors
- Three actuating directions so that there is only one version for rotating and sliding guards
- Degree of protection IP69
- High tolerance to door misalignment
- Holding force  $F_{Zh}$  1,150 N /  $F_{max}$  1,500 N, switchable latching force (25 N / 50 N)
- PL e / Cat. 4 according to EN ISO 13849-1 / SIL 3 according to IEC 61508
- Series-wiring without reduction of the safety level
- More than 30,000 different codings
- Serial diagnostic
- Power to lock or power to unlock
- Actuator or solenoid interlock monitoring
- With integrated AS interface, AS-i Power, AUX Power
- Emergency exit -T for use within the hazardous area
- Emergency release -N for use outside the hazardous area

Code number: AZM300

UKCA, AS-i, TÜV, cULus, CE

## MZM 100 – Solenoid interlock



- Unique working principle for solenoid interlocks (for personal protection functions)
- 40 mm x 179 mm x 40 mm
- Fine-adjustment through slotted holes
- Can be used as an end stop
- Locking force 750 N (typically) / 500 N (guaranteed), continuously monitored
- Variably adjustable latching
- Contact-free, coded electronic system
- Sensor technology permits an offset between actuator and interlock of  $\pm 5$  mm vertically and  $\pm 3$  mm horizontally
- Intelligent diagnosis
- Series-wiring without reduction of the safety level
- Power to lock
- Actuator or solenoid interlock monitoring
- With integrated AS interface
- Degree of protection IP67

Code number: MZM 100

AS-i, TÜV, cULus, CE

## AZM 201 – Solenoid interlock



- Holding force  $F_{Zh} = 2,000$  N /  $F_{max}$ : 2,600 N
- Thermoplastic enclosure
- Sensor technology permits an offset of  $\pm 5$  mm between actuator and interlock
- Non-contact, coded electronic RFID system with a high level of protection against manipulation according to EN ISO 14119
- Series-wiring without reduction of the safety level
- Intelligent diagnosis
- PL e / Cat. 4 according to EN ISO 13849-1 / SIL 3 according to IEC 61508
- Optionally with emergency exit or emergency release
- Degree of protection IP66, IP67
- With integrated AS interface
- Suitable for hinged and sliding guards
- 100% drop-in replacement for predecessor model AZM 200

Code number: AZM201

AS-i, TÜV, cULus, CE

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

## RSS 16 – Safety sensor



- Coding level “high” according to EN ISO 14119 with an individual RFID code
- Three encoding options for demand-protection against manipulation
- Three directions of actuation for sliding and rotating doors
- Optionally with door stop with magnetic latching function, latching force 40/60 N
- Latching space and connector
- Suitable for series-wiring
  - up to PL e / Cat. 4 to EN ISO 13849-1
  - and SIL 3 to IEC 61508
- Optional for areas at risk of explosion
  - IECEx, ATEX
  - Category 3D and 3G
  - Ex tc (dust), Ex ec (gas)

Code number: RSS 16

ATEX, AS-i, TÜV, cULus, CE

## RSS 36 – Safety sensor



- Coding level “high” according to EN ISO 14119 with an individual RFID code
- Intelligent non-contact door monitoring with a high level of protection against manipulation
- Electronic safety-sensor
- Repeated universal or individual coding
- High tolerance to horizontal and vertical misalignment with pre-indication in hysteresis area
- Optionally with integrated magnetic latching
- Suitable for applications
  - up to PL e / Cat. 4 to EN ISO 13849-1
  - and SIL 3 to IEC 61508
- Degree of protection IP69
- With optional integrated AS interface

Code number: RSS 36

AS-i, TÜV, cULus, CE

## RSS 260 – Safety sensor



- Intelligent non-contact door monitoring with a high level of protection against manipulation
- Coding level “high” according to EN ISO 14119 with an individual RFID code
- Three encoding options for demand-protection against manipulation
- Compact design and subtle, elegant design
- Easy installation without additional angles
- Universal application through different targets for typical installation situations
- Preservation of safety levels and diagnostic capability even when connected in series
- With optional integrated AS interface
- Three different actuators available

Code number: RSS 260

ECOLAB, AS-i, TÜV, cULus, CE

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

# GUARD DOOR MONITORING

## CSS 30S – Safety sensor



- Rugged stainless steel housing 1.4404, M30
- Two short-circuit proof PNP safety outputs (24 VDC, 250 mA each)
- Up to 31 safety sensors can be wired in series, self-monitoring
- Integrated cross-wire short and external voltage monitoring of the safety outputs
- Integrated connector M12, 8-pin
- Degree of protection IP69
- Concealed mounting behind stainless steel possible
- PL e / Cat. 4 according to EN ISO 13849-1 / SIL 3 according to IEC 61508
- Extensive serial diagnostic functions

Code number: CSS 30S

TÜV, cULus, CE

## BNS 40S – Safety sensor



- Stainless steel enclosure
- With coding
- Rectangular design
- Long life, no mechanical wear
- Degree of protection IP69
- Insensitive to transverse misalignment
- Concealed mounting behind stainless steel possible
- Insensitive to soiling
- Connecting cable suitable for the food-processing industry
- Ex-version

Code number: BNS 40S

ATEX, ECOLAB, cULus, CE

## RM 40S – Magnetic stopper for ease of cleaning



- Door hinge with magnetic latching 25 N / 35 N / 60 N
- Housing completely enclosed in stainless steel
- Different directions of actuation
- Easy to clean and is rugged
- Rear sided thread M4 or through holes
- Ideal accessory for BNS 40S

Code number: RM40S

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

## PS – Position switch family



- Series PS116, PS2xx and PS3xx
- Compact metal and thermoplastic enclosure
- Connecting cable or connector plug M12, on the side / below
- Different easily replaceable actuators, adjustable in 15° steps
- Actuator element in 8 x 45° can be implemented
- Degree of protection IP66, IP67
- Slow action or snap action
- Switching elements with up to 3 contacts – NO contacts and/or NC contacts
- Redundant switch-off with positive break normally-closed contacts with additional signaling contact

Code number: PS

UKCA, TÜV, CCC, cULus, CE

## TESK – Hinge safety switch



- Freely adjustable switching angle or preset
- Large swivel angle of 270°
- Optimised for profile system
- With long hinge halves special for combining with plastic doors
- With up to 4 contacts
- Metal enclosure
- Connecting cable or connector plug M12, on the side / below

Code number: TESC

CCC, cULus, CE

## BDF 200 – Universal Control Panel



### Emergency-Stop and 3 command and signalling devices

- Control panel with Emergency-Stop function and 3 mounting positions for command and signalling devices
- Large range of illuminated pushbuttons, selector switches, LED indicators, key-operated switches, Emergency-Stop buttons
- Emergency-Stop, start/stop and reset functions available
- Optional integrated AS interface, AS-i Power
- Optionally highly-visible indicator lamp G24 (red / green) optional
- Emergency-Stop suitable for applications
  - up to PL d / Cat. 4 to EN ISO 13849-1
  - and SIL 3 to IEC 61508
- Degree of protection IP65
- Dimensions: 40 mm x 244 mm x 50 mm
- Optionally with electronic Emergency-Stop function with OSSD
- Plug and play solution for connection to the safety fieldbox

Code number: BDF 200

AS-i, TÜV, cULus, CE

Detailed information about the products can be found at [products.schmersal.com](https://products.schmersal.com) below the indicated code numbers

# OPTOELECTRONIC SAFETY TECHNOLOGY/AUTOMATION

## SLC/SLG 440/440COM – Safety light curtains Type 4 with protective enclosure SH/PH



- Hygienic design
  - End caps, mounting and membrane made of stainless steel V4A
- High degree of protection IP69, 2-part O-ring seal
- Break and shock-resistance protective tube made of polycarbonate
- Connection with M12x1 4-pin or 8-pin, cable length 10 m
- Process reliability with daily cleaning
- Integrated set-up tool
- Resolution 14 mm ... 30 mm
- Range 0.3 m ... 20 m
- Suitable for applications in PL e / SIL 3
- Integrated Bluetooth interface

Code number: Protective enclosure

ECOLAB, TÜV, cULus, CE

## SLC/SLG 440/445 – Safety light curtains and safety light grids



- Can be adapted to any application due to the functional diversity:
  - muting, cyclic operation, object muting, dual acknowledgment
- Parameterisation with a single button, without external aids (PC / software)
- Set-up assistance integrated resulting in reduced mounting work and reduced costs
- High degree of protection IP67
- Optional integrated AS-I Safety at Work interface
- Resolution 14 mm ... 30 mm
- Range 0.3 m ... 20 m
- Area protection with up to 4 emitters
- Suitable for applications in PL e / SIL 3
- Integrated Bluetooth interface

Code number: SLC and SLG

EAC, AS-i, TÜV, cULus, CE

## SLB 240/440 – Safety light barriers



**GIT  
SICHERHEIT  
AWARD  
2018  
WINNER**

- **SLB240/440**
  - Integrated evaluation, status and diagnostic display
  - Range 15 m
  - Coding adjustable without aids/PC
  - Suitable for applications to Cat. 4 / PL e / SIL 3
  - Degree of protection IP67, ambient temperature -30 °C ... +50 °C
  - W x D x H: 28 x 33 x 72 / 91 mm
- **SLB440-H**
  - Range 75 m
  - Suitable for applications to Cat. 4 / PL e / SIL 3
  - Degree of protection IP67, ambient temperature -30 °C ... +50 °C
  - W x D x H: 28 x 33 x 111 / 131 mm
  - Integrated evaluation, status and diagnostic display
  - Optional heater for low temperature ranges

Code number: SLB

TÜV, cULus, CE

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

# COMMAND AND SIGNALLING DEVICES

## Hygiene-compliant control devices and indicator lights range N



- Special sealing measures prevent the ingress of dirt into the gaps and aids in thorough cleaning of the operating and display elements
- Suitable for low voltage  $\geq 5\text{ V} / 3.2\text{ mA}$ .
- Mounting holes 22.3 mm, with adapter 30.5 mm
- Degree of protection IP67, IP69
- Pushbutton, short stroke button
- Mushroom button, illuminated signal, illuminated button with LEDs
- Selector switch with 2 and 3 positions and short and long knob
- Emergency-Stop command device with mechanical latching function
- Lockable mounting frame for maintained selector switch
- Screw terminals, blade terminal, cage clamp terminals or PCB connection
- Potentiometer drive

DGUV, CE

### Emergency-Stop command device $\varnothing 50\text{ mm}$



- According to IEC 60947-5-5, EN ISO 13850
- With optional protective cover V4A
- Bellows: white, black, blue

Code number: NDRR

### Mushroom head impact button/ Mushroom push button $\varnothing 50\text{ mm}$



- Bellows: white, black, blue
- Different colours available

Code number: NDP

### Maintained selector switches / spring-return selector switches



- Optional short or long knob
- Colours: white, grey or black

Code number: NWS / NWT

### Illuminated pushbutton



- High luminosity due to integrated multi-LED
- Different colours available
- Bellows: white, black, blue

Code number: NDL

### Indicator lights



- "Super-bright" LED in integrated device head
- Different colours available
- Surface or high collar

Code number: NME / NML

### 3 colour LED



- LED illumination element red, green, yellow in one device
- Colours can be controlled separately

Code number: ELDE.N-RD-GN-YE

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

# COMMAND AND SIGNALLING DEVICES

## NDLP30 Ø 30 mm Illuminated pushbutton



- Mushroom pushbutton with improved ergonomics
- With and without illumination
- Bellows: white, black, blue

Code number: NDLP

## Step selector switch



- 3 to 12 switch positions
- One NO contact per stage
- IP69

Code number: NWSE

## Potentiometer drive



- To accommodate standard potentiometers
- IP69

Code number: NDAN

## NBG Assembly housing



- Stainless steel enclosure V4A
- Degree of protection IP69
- Optionally available as Ex-version

Code number: NBG

## Mounting flange with position switch



- PS116 in conjunction with device heads of series N and E
- Specially for Emergency-Stop impact buttons – Degree of protection IP69 in front of the front panel and IP67 behind the front panel

Code number: EFMH

## Joystick switches NK / RK



- 2 ... 4 actuating directions
- NK: Food industry, hygienic
- RK: Outdoor area, plant technology
- IP67, IP69 in front of front panel
- Temperature range from -40 °C ... +80 °C

Code number: NK-T

## Main switch 3 pin



- Versions 40A and 63A
- With red or black toggle
- Quadratic V4A mounting plate

Code number: NHSNH63

## Main switch 2/4 pin



- Versions 16A
- With red or black toggle
- V4A mounting plate 70 x 80 mm, Ø100

Code number: NHS16/2

## Accessories: Emergency-Stop protective collar



- Bracket material 1.4550, stainless steel plate V4A powder-coated

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

# SAFE SIGNAL PROCESSING

## Safety monitoring PROTECT SRB-E...



Code number: SRB-E

- User friendly
  - Multi-functional evaluation switches
  - Up to 11 different freely adjustable applications
  - Connection for all standard safety switching devices up to PL e according to EN ISO 13849-1
  - Wear-free switching via safe semiconductor outputs
  - Very short on-demand response times 10 ms
  - Easy adjustment via rotary switch
  - Intelligent diagnostic and status messages via LED displays
  - Pluggable connection technology
- Powerful versions
  - Up to 5 safety outputs (relay technology / semiconductor technology)
  - Input extension for monitoring 4 safety relays (up to PL e)
  - Relay module can be cascaded via the safety inputs
  - Two safety functions each with 2 safety outputs
  - Powerful p-type safe semiconductor outputs up to 5.5 A

TÜV, CCC, cULus, CE

## PROTECT SELECT



Code number: PROTECT-SELECT

- User friendly
  - Simple and flexible parameterisation
  - Multilingual menu navigation via colour display
  - Error and status messages in plain text
- Compact
  - Replaces up to 8 safety-monitoring modules up to PL e / SIL 3
  - Compact safety technology in 52 mm enclosure
  - 18 safe inputs for redundant query of all common safety sensors such as Emergency-Stop, light grids, safety switches, safety mats, etc.
  - 4 safe semiconductor outputs
  - 2 safe relay outputs
  - 4 optional signaling outputs
- Customer specific programs

TÜV, CCC, cULus, CE

## PROTECT PSC1



Code number: PSC1

- Safe type-tested logic control according to Annex IV of the Machinery Directive 2006/42/EC
- Connection for all standard safety relays up to PL e according to EN ISO 13849-1
- Modular expansion with up to 272 inputs / outputs
- Secure 2A double p-type semiconductor outputs, switchable to secure p- / n-switching semiconductor outputs
- Freely programmable inputs / outputs
- Safe drive monitoring according to EN 61800-5-2 (SDM – Safe Drive Monitoring) for up to 12 axes
- Universal communication module:
  - Supports standard field bus systems including the safety protocols
  - Setting and resetting of field bus protocols by software
  - Safety Remote IOs
  - Safe cross-communication
- Schmersal SD-Bus-Interface integrated

TÜV, cULus, CE

Detailed information about the products can be found at [products.schmersal.com](http://products.schmersal.com) below the indicated code numbers

# THE SCHMERSAL GROUP

## PROTECTION FOR MAN AND MACHINE

In the demanding field of machine safety, the owner-managed Schmersal Group is one of the international market leaders. The company, which was founded in 1945, has a workforce of about 2,000 people and seven manufacturing sites on three continents along with its own companies and sales partners in more than 60 countries.

Customers of the Schmersal Group include global players from the area of mechanical engineering and plant manufacturing as well as operators of machinery. They profit from the company's extensive expertise as a provider of systems and solutions for machine safety. Furthermore, Schmersal specialises in various areas including food & beverage, packaging, machine tools, lift switchgear, heavy industry and automotive.

A major contribution to the systems and solutions offered by the Schmersal Group is made by tec.nicum with its comprehensive range of services: Certified Functional Safety Engineers advise machinery manufacturers and machinery operators in all aspects relating to machinery and occupational safety – and do so with product and manufacturer neutrality. Furthermore, they design and realise complex solutions for safety around the world in close collaboration with the clients.



### SAFETY PRODUCTS

- Safety switches and sensors, solenoid interlocks
- Safety controllers and safety relay modules, safety bus systems
- Optoelectronic and tactile safety devices
- Automation technology: position switches, proximity switches

### SAFETY SYSTEMS

- Complete solutions for safeguarding hazard areas
- Individual parametrisation and programming of safety controllers
- Tailor-made safety technology – be it for individual machines or a complex production line
- Industry-specific safety solutions

### SAFETY SERVICES

- tec.nicum academy – Seminars and training
- tec.nicum consulting – Consultancy services
- tec.nicum engineering – Design and technical planning
- tec.nicum integration – Execution and installation



x.000 / L+W / 08.2022 / Teile-Nr. 103011512 / EN / Ausgabe 03