

OUR 12 MODELS FOR EXTENSIVE AND INTENSIVE FARMING

MONOCOQUE TRAILERS

RANGE **FIRST**



The arm of the door is in DOMEX EXTRA H.L.E.

maximum tipping angle 51°

The outriggers of the chassis are made of EXTRA H.L.E. rectangular tubing 300 x 100 mm.

FIRST 1732



Joint on the internal side of the door

Door cylinder with dual steered valves



Cover (optional)



Angle at 135° in order to avoid any deposition of residue.

The outriggers of the body frame are made of EXTRA H.L.E. rectangular tubing 200 x 100 mm.

Central reinforcement at the bottom of the trailer made of DOMEX steel profiles.



roudenng Grafik, PLEINM 02 96 56 02 03



FIRST 2440



FIRST 1732

YOUR DEALER

Z. I. DE GRACES - 22200 GUINGAMP
Phone : + 33 (0) 2 96 43 40 62 Fax : +33 (0) 2 96 43 66 57
com@remorques-chevance.eu

www.remorques-chevance.com



We strive for continuous improvement of our machines therefore we reserve the right to modify their technical characteristics without any notice. This is a non-binding document. Materials comply with EC safety rules. All materials are approved by appropriate authorities.



Remorques chevance

Single axle version



FIRST 1124

Silage sides in aluminium



FIRST 1530

Two-axes version



FIRST 1834

Three-axes version



FIRST 2441

Top tail of the reinforced and sealed body frame

Long studs to ensure better resistance and robustness.

Standard front window 0,38*0,40



Cereal front window 1,40*0,40



Beet front window 1,85*0,55



Trailer's cylinder with high tipping capacity

FIRST 19536

Mechanical locking



Steel sides folded in one sole piece



Chassis SWEDISH STEEL STRENX (parts in red on the drawing)



FIRST 2440

PRODUCTS' CHARACTERISTICS

	Carrying capacity (Tons)	Gross Vehicle Weight Rating (Tons)	Body frame dimensions (meters)			Volume (m³) Sides 1,50 m	Volume (m³) Sides 1,80	Volume (m³) Sides 2,20 m	Axles
			Length (bottom part)	Length (top part)	Width				
FIRST 11/24	11	14,10	4,50	4,90	2,25	16	19	24	Axle 110
FIRST 13/26	13	16,86	5,00	5,40	2,25	17,50	21	26	Boggie 90
FIRST 15/30	15	19,79	5,60	6,00	2,25	20	24	30	Boggie 100
FIRST 17/32	17	22,80	6,00	6,40	2,25	22	26	32	Boggie 110
FIRST 18/34	18	24	6,50	6,90	2,25	24	29	34	Boggie 130
FIRST 19/34	19	25	6,50	6,90	2,25	24	29	34	Boggie 130

PRODUCTS' CHARACTERISTICS

	Carrying capacity (Tons)	Gross Vehicle Weight Rating (Tons)	Body frame dimensions (meters)			Volume (m³) Sides 1,50 m	Volume (m³) Sides 1,80	Volume (m³) Sides 2,20 m	Axles
			Length (bottom part)	Length (top part)	Width				
FIRST 185/36	18,5	24	7,00	7,40	2,25	26	30,50	36,50	Boggie 130
FIRST 195/36	19,5	25	7,00	7,40	2,25	26	30,50	36,50	Boggie 130
FIRST 21/39	21	29	7,50	7,90	2,25	27	32	39	Tandem with rods
FIRST 22/39	22	30	7,50	7,90	2,25	27	32	39	Tandem with rods
FIRST 24/40	24	32	7,50	7,90	2,25	27	32	40	Tridem with rods
FIRST 24/41	24	32	7,90	8,30	2,25	28	33	41	Tridem with rods