

Speed StackerGantry Robot






The perfect tool to meet the need **for wide area stacking!**

- √ 400 or 600kg lifting capacity
- ✓ Lifting movements up to 1 m/s
- ✓ Traversing movements up to 2 m/s
- √ Stacking/sorting **over a large area**
- ✓ **Instant picking and release** of the boards
- ✓ Warm air backflow for extreme and cold environments
- ✓ Easy and low maintenance




360° Rotation



Technical Data

- 4 axis (lifting, cross and length movements, 360° rotation)
- SEW CM3C Servomotors and Gen C inverters
- Transmission with Timing Belt and Polyurethane wheels
- Radiocommand with EtherCat protocol
- · Lifting movement with linear guiding system
- On-board electrical control box
- Filtering system for wet and dusty environemts


SPEED STACKER



High speed stacking and sorting

Characteristics / Standards	Speed Stacker 400	Speed Stacker 600
Length of boards	standard	reinforced
Weight of boards	7000mm	10000mm
Height of stack	400kg	600kg
Gripper dimensions	1600 to 2000mm	
Lifting Axis - linear bearing guide or urethane roller	2 grippers 100x650mm	2 grippers 100x900mm
Filter rating	ball-bearing guide	roller guide
Air Filter	5μ	
Maintenance access	option	
Servo motor power rating	4 doors with gas springs	
High pressure vacuum blower	7,5kW	11kW
Radio control	5,5kW	7,5kw
Turbine à haut niveau de vide	-700mBar	
Radiocommande	IP65 protection rating	

Ergonomic and compact Radio-Command

















Filtering system for wet and dusty environments



Polyurethane wheels



SEW Gen C inverters

4 - Joulin - Speed Stacker - 5



USA

2551 Hwy 70 SW - HICKORY NC-28602

Phone: +(1) 828 327 2290 Fax: +(1) 828 327 8678

France

17 avenue des Grenots F-91150 ETAMPES

Tél. +33 (0)1 69 92 16 16 Fax +33 (0)1 64 94 21 35



contact: wood@joulin.com
www.joulin.com