



DIVINA



argenta





SWING DOOR

Thanks to pure lines and invisible hinges, the divina® swing door is the solution for a minimalist eye-catcher in any interior. The optional subdivisions make every interior unique.

USPs

MINIMALIST PROFILES

- Height: 35 mm

FLOOR-TO-CEILING SWING DOOR

- Integration invisible tyo
- Magnotica® pro invisibly concealed

MODULAR AND FLEXIBLE SYSTEM

- Both standard and floor-to-ceiling application
- Easily shortened

Specifications

GLASS THICKNESS

- 8 to 10 mm in tempered glass
- 44.2 to 55.2 in laminated glass

DIMENSIONS

- Max. door height = 3000 mm
- Max. door width = 1000 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey



DOUBLE REVOLVING DOOR

A passively locked door and an active door together form a minimalist solution for practical double revolving doors.

USPs

MINIMALISTIC

- Active and passive door with the same slim profiles
- Equipped with a slam post between both doors
- Passive door equipped with an invisible lock

USER-FRIENDLY

- Inconspicuous slider to unlock the top and bottom flush bolt

MODULAR AND FLEXIBLE SYSTEM

- Both standard and floor-to-ceiling application
- Easily shortened
- Can be combined with a fixed wall.

Specifications

GLASS THICKNESS

- 8 to 10 mm in tempered glass
- 44.2 to 55.2 in laminated glass

DIMENSIONS

- Max. door height = 3000 mm
- Max. door width = 1000 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey



FIXED WALL

Thanks to divina® glass walls, spaces are easily divided without loss of light or openness. The innovative aluminium structure and glass provide an industrial, minimalist look that fits perfectly in homes, hotels, and restaurants.

USPs

MINIMALIST PROFILES

- Height: 35 mm

SIMPLE AND FAST INSTALLATION

- One profile for different glass thicknesses
- Unique and intuitive click system suitable for different glass thicknesses

MODULAR AND FLEXIBLE SYSTEM

- Both standard and floor-to-ceiling application
- Easily shortened
- Allows for 5 mm adjustment horizontally and vertically

Specifications

GLASS THICKNESS

- 6 to 10 mm in tempered glass
- 33.1 to 55.2 in laminated glass

DIMENSIONS

- Max. height = 3000 mm
- Max. width = 6000 mm
- Max. width per glass plate = 1500 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey



FIXED WALL WITH SIDE POST

An end post offers the option of closing only part of the room with a fixed wall. Ideal to place next to a passage or to divide catering establishments into cosy sitting areas.

USPs

MINIMALIST PROFILES

- Height: 35 mm
- Side post: 35 mm

SIMPLE AND FAST INSTALLATION

- One profile for different glass thicknesses
- Unique and intuitive click system suitable for different glass thicknesses

MODULAR AND FLEXIBLE SYSTEM

- Both standard and floor-to-ceiling application
- Easily shortened
- Allows for 5 mm adjustment horizontally and vertically

Specifications

GLASS THICKNESS

- 6 to 10 mm in tempered glass
- 33.1 to 55.2 in laminated glass

DIMENSIONS

- Max. height = 3000 mm
- Max. width = 6000 mm
- Max. width per glass plate = 1500 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey



FIXED WALL WITH SWING DOOR

Thanks to the invisibly integrated argenta tyo hinges and magnetic lock, all the attention is focused on the design's clean lines.

USPs

FLOOR-TO-CEILING SWING DOOR

- Integration invisible tyo
- Magnotica® pro invisibly concealed

MINIMALIST PROFILES

SIMPLE AND FAST INSTALLATION

- One single profile for different glass thicknesses
- Unique and intuitive click system for glass thickness

MODULAR AND FLEXIBLE SYSTEM

- Both standard and floor-to-ceiling application
- Easily shortened
- Allows for 5 mm adjustment horizontally and vertically

Specifications

GLASS THICKNESS

- 8 to 10 mm in tempered glass
- 44.2 to 55.2 in laminated glass

DIMENSIONS

- Max. height = 3000 mm
- Max. width = 6000 mm
- Max. width per glass plate = 1500 mm
- Max. door width = 1000 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey





SLIDING DOOR

A sliding door in line with its underlying wall.

USP's

MINIMALISTIC PROFILES

- Integrated running track in the ceiling: The top profile of the door is at the same height as its underlying profile of the fixed wall.
- Both sides of the sliding door have an identical finish.

FLEXIBLE SLIDING SYSTEM

- Sliding system and door can be combined with divina® wall or another wall.
- Stoppers or soft closers ensure the stopping positions of the rollers, and the position can be quickly adjusted with a simple turn.
- Completely invisible floor guide.

EASY AND FAST INSTALLATION

- Glass is clamped all around by its profiles, allowing for a strong connection between the profile and rollers.
- The glass can be replaced without causing damage to the profiles.

Specifications

GLASS THICKNESS

- 8 to 10 mm in tempered glass
- 44.2 to 55.2 in laminated glass

DIMENSIONS

- Max. height = 3000 mm
- Max. width = 6000 mm
- Max. width per glass plate = 1500 mm
- Max. door width = 1000 mm

OPTIONS

- Self-adhesive, freely positionable crossbars
- In black, white and grey



CORNER UNIT

The corner profile offers the possibility to connect walls and build complete rooms. The slim corner profile is only 38 mm wide.

USPs

MINIMALIST PROFILES

- Extremely narrow corner profile so that you see no difference from the front compared to the other profiles used.

MODULAR AND FLEXIBLE SYSTEM

- Glass is placed or mounted by a quick click and this also in the corner
- Offers the possibility to build complete rooms with divina®

AVAILABLE IN
3 DIFFERENT COLOURS


WHITE TXT9016



GREY TXT7016



BLACK TXT9005



OPTIONAL
CYLINDER LOCK

WHITE TXT9016



GREY TXT7016



BLACK TXT9005



WITH A
STYLISH HANDLE

WHITE TXT9016




GREY TXT7016



BLACK TXT9005



CONFIGURE YOUR OWN DIVINA
OPTIONAL WITH CROSSBAR PROFILES



ARLU[®]
OPENING DOORS

Ter Vlucht 2
8850 Ardoonie
Belgium

+32 (0)51 27 05 00
info@arlu.be
WWW.ARLU.BE



©L2001417 11/23 EN